

響ホール DMX対応表

2023 3.15

青字=DIM

=灯体アドレス

赤字=直/調切替

DMX		DMX		DMX		DMX		DMX		DMX		DMX		DMX		DMX									
1	1SUS	1	61	9	121	G	181	G	241	G	301	Am	361	Am	421	I	481								
2		2	62	10	122	B	182	B	242	B	302	Li	362	Li	422	L	482								
3		3	63	11	123	LB	183	LB	243	LB	303	G	363	G	423	strb	483								
4		4	64	12	124	W	184	W	244	W	304	Cy	364	Cy	424	LED PAR-10	INT	484							
5		5	65	SC 下	1	125	INT	185	INT	245	INT	305	B	365	B	425	3SUS	R	485						
6		6	66		2	126	UH 3	R	186	LH 1	R	246	I	366	I	426		G	486						
7		7	67		3	127		G	187	下→	G	247		367	strb	427		I	487						
8		8	68		4	128		B	188		B	248		368	Cur	428		L	488						
9		9	69		5	129		LB	189		LB	249		369	Fan	429		strb	489						
10		10	70		6	130		W	190		W	250		310	LEDソースF-2	INT	370	LED PAR-1	INT	430	LED PAR-11	INT	490		
11		11	71		7	131		INT	191		INT	251		311	下中	DR	371	1SUS	R	431	3SUS	R	491		
12		12	72		8	132	UH 4	R	192	LH 2	R	252		312		R	372		G	432		G	492		
13	2SUS	1	73		9	133		G	193		G	253		313		Am	373		I	433		I	493		
14		2	74	SC 上	1	134		B	194		B	254		314		Li	374		L	434		L	494		
15		3	75		2	135		LB	195		LB	255		315		G	375		strb	435		strb	495		
16		4	76		3	136		W	196		W	256		316		Cy	376	LED PAR-2	INT	436	LED PAR-12	INT	496		
17		5	77		4	137		INT	197		INT	257		317		B	377	1SUS	R	437	3SUS	R	497		
18		6	78		5	138	UH 5	R	198	LH 3	R	258	天1	1	1	318		I	378		G	438		G	498
19		7	79		6	139		G	199		G	259		2	2	319		strb	379		I	439		I	499
20		8	80		7	140		B	200		B	260		3	3	320		Cur	380		L	440		L	500
21		9	81		8	141		LB	201		LB	261		4	4	321		Fan	381		strb	441		strb	501
22		10	82		9	142		W	202		W	262		5	5	322	LEDソースF-3	INT	382	LED PAR-3	INT				502
23		11	83	前C	1	143		INT	203		INT	263		6	6	323	下内	DR	383	1SUS	R	443			503
24		12	84		2	144	UH 6	R	204	LH 4	R	264		7	7	324		R	384		G	444			504
25	3SUS	1	85		3	145		G	205		G	265		8	8	325		Am	385		I	445			505
26		2	86	後C	1	146		B	206		B	266		9	9	326		Li	386		L	446			506
27		3	87		2	147		LB	207		LB	267		10	10	327		G	387		strb	447			507
28		4	88		3	148		W	208		W	268		11	11	328		Cy	388	LED PAR-4	INT	448			508
29		5	89	客電 プロセ	1	149		INT	209		INT	269	天2	1	12	329		B	389	1SUS	R	449			509
30		6	90	か列	2	150	UH 7	R	210	LH 5	R	270		2	13	330		I	390		G	450			510
31		7	91	さ列	3	151		G	211		G	271		3	14	331		strb	391		I	451			511
32		8	92	ち列	4	152		B	212		B	272		4	15	332		Cur	392		L	452			512
33		9	93	ぬ列	5	153		LB	213		LB	273		5	16	333		Fan	393		strb	453			
34		10	94	BC下	6	154		W	214		W	274		6	17	334	LEDソースF-4	INT	394	LED PAR-5	INT	454			
35		11	95	BC上	7	155		INT	215		INT	275		7	18	335	上外	DR	395	2SUS	R	455			
36		12	96	下	8	156	UH 8	R	216	LH 6	R	276		8	19	336		R	396		G	456			
37	バルコニー下	1	97	中	9	157		G	217		G	277		9	20	337		Am	397		I	457			
38		2	98	上	10	158		B	218		B	278		10	21	338		Li	398		L	458			
39		3	99	3FBK 下	1	159		LB	219		LB	279		11	22	339		G	399		strb	459			
40		4	100	3FBK 上	2	160		W	220		W	280	天3	1	23	340		Cy	400	LED PAR-6	INT	460			
41	バルコニー上	1	101	1FBK 下	1	161		INT	221		INT	281		2	24	341		B	401	2SUS	R	461			
42		2	102	1FBK 上	2	162	UH 9	R	222	LH 7	R	282		3	25	342		I	402		G	462			
43		3	103	バルコニー天	上下	163		G	223		G	283		4	26	343		strb	403		I	463			
44		4	104	側面反射板	スジ	164		B	224		B	284		5	27	344		Cur	404		L	464			
45	FR 下 最	1	105	予備 1		165		LB	225		LB	285		6	28	345		Fan	405		strb	465			
46		2	106	予備 2		166		W	226		W	286		7	29	346	LEDソースF-5	INT	406	LED PAR-7	INT	466			
47		3	107	BL 全16灯	R	167		INT	227		INT	287		8	30	347	上中	DR	407	2SUS	R	467			
48		4	108		G	168	UH 10	R	228	LH 8	R	288		9	31	348		R	408		G	468			
49	FR 上 最	1	109		B	169		G	229		G	289	天4	1	32	349		Am	409		I	469			
50		2	110		LB	170		B	230		B	290		2	33	350		Li	410		L	470			
51		3	111		W	171		LB	231		LB	291		3	34	351		G	411		strb	471			
52		4	112		INT	172		W	232		W	292		4	35	352		Cy	412	LED PAR-8	INT	472			
53	CL	1	113		strb	173		INT	233		INT	293		5	36	353		B	413	2SUS	R	473			
54		2	114	UH 1	R	174	UH 11	R	234	LH 9	R	294		6	37	354		I	414		G	474			
55		3	115	下→	G	175		G	235		G	295		7	38	355		strb	415		I	475			
56		4	116		B	176		B	236		B	296		8	39	356		Cur	416		L	476			
57		5	117		LB	177		LB	237		LB	297		9	40	357		Fan	417		strb	477			
58		6	118		W	178		W	238		W	298	LEDソースF-1	INT	358	LEDソースF-6	INT	418	LED PAR-9	INT	478				
59		7	119		INT	179		INT	239		INT	299	下外	DR	359	上内	DR	419	3SUS	R	479				
60		8	120	UH 2	R	180	UH 12	R	240	LH 10	R	300			360		R	420		G	480				

空き
P1=442~512
P2=513~
1024